



TXL Teres Elite
Full Synthetic Motor Oil; SAE 0W-20
API SN, ILSAC GF-5

Product Description

TXL Teres Elite Full Synthetic Motor Oils, SAE 0W-20, API SN, ILSAC GF-5 is formulated with synthetic base oils and a premium additive package. This oil is designed for use in carbureted, fuel injected, turbocharged gasoline engines. This oil exceeds the performance requirements of API SN and ILSAC GF-5.

Typical Properties*

SAE J300 Viscosity Grade	0W-20
Appearance	Amber, Transparent Liquid
Viscosity @ 40° C, cSt, ASTM D445	44.55
Viscosity @ 100° C, cSt, ASTM D445	8.3
Viscosity Index, ASTM D2270	165
CCS Apparent Viscosity, cP, ASTM D5293	5,400@-35°C
MRV Apparent Viscosity, cP, ASTM D4684	22,000@-40°C
Flash Point, °C, ASTM D92	215
Pour Point, °C, ASTM D97	-48

**The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.*

Exceeds Performance Requirements

API SN with Resource Conserving, API SM, API SL, API SJ
ILSAC GF-5
Chrysler MS6395
Ford WSS-M2C947-A



