



PRODUCT DATA SHEET

TXL Teres
SAE 10W-40, 20W-50
Synthetic Motor Oil; API SN

Product Description

TXL Teres Synthetic Blend Motor Oils, SAE 10W-40 and 20W-50 API SN Plus are formulated with a blend of conventional and synthetic base oils and a premium additive package. These oils are designed for use in carbureted, fuel injected, turbocharged and supercharged gasoline engines in both normal and extreme operating conditions. These oils exceed the performance requirements of API SN.

Typical Properties*

SAE J300 Viscosity Grade	10W-40	20W-50
Appearance, Visual	Amber, Transparent, Liquid	
Viscosity @ 40° C, cSt, ASTM D445	100.25	160.55
Viscosity @ 100° C, cSt, ASTM D445	14.5	18.5
Viscosity Index, ASTM D2270	150	130
CCS Apparent Viscosity, cP, ASTM D5293	5,600@-25°C	5,900@-15°C
MRV Apparent Viscosity, cP, ASTM D4684	21,000@-30°C	15,600@-20°C
Flash Point, °C, ASTM D92	215	220
Pour Point, °C, ASTM D97	-40	-30

**The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.*

Exceeds Performance Requirements

API SN, API SM, API SL, API SJ

