



TXL Teres
SAE 5W-20, 5W-30 & 10W-30
Synthetic Motor Oil; API SN, ILSAC GF-5

Product Description

TXL Teres Synthetic Motor Oils, SAE 5W-20, 5W-30, and 10W-30, API SN, ILSAC GF-5 are formulated with a blend of conventional and synthetic base oils and a premium additive package. These oils are designed for use in carbureted, fuel injected, turbocharged gasoline engines. These oils exceed the performance requirements of API SN and ILSAC GF-5

Typical Properties*

SAE J300 Viscosity Grade	5W-20	5W-30	10W-30
Appearance, Visual	Amber, Transparent, Liquid		
Viscosity @ 40° C, cSt, ASTM D445	48.95	62.8	70.7
Viscosity @ 100° C, cSt, ASTM D445	8.3	10.8	10.9
Viscosity Index, ASTM D2270	145	165	145
CCS Apparent Viscosity, cP, ASTM D5293	5,000@-30°C	5,400@-30°C	5,000@-25°C
MRV Apparent Viscosity, cP, ASTM D4684	18,000@-35°C	21,000@-35°C	9,800@-30°C
Flash Point, °C, ASTM D92	210	210	215
Pour Point, °C, ASTM D97	-44	-42	-40

**The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.*

Exceeds Performance Requirements

API SN, API SM, API SL, API SJ

ILSAC GF-5

Chrysler MS6395

GM6094M

Ford WSS-M2C946-A (5W-30); Ford WSS-M2C945-A (5W-20)

