



TEXAS LUBE

Texas Frictio 4t (Four Stroke) Synthetic Blend Engine Oil SAE 10W-30, 10W-40, 20W-50 API SL, JASO MA2

Product Description

Texas Frictio Synthetic Blend Engine Oils 4T (Four-Stroke) are Para synthetic, high-performance, multi-grade lubricants for use in high-RPM, 4-stroke motorcycle engines with integral gear boxes and wet clutches as well as for use in any application requiring a four-stroke engine oil meeting the requirements of JASO MA2, JASO MA or API SN. Blended with synthetic base stocks and premium performance additives, Texas Frictio Synthetic Blend Engine Oils 4T (Four-Stroke) provide excellent protection during rapid RPM increase. Specialty friction modifiers provide for smooth clutch and gear shift operation while specialty anti-oxidants and sophisticated dispersant technology provide enhanced cleanliness. Texas Frictio Synthetic Blend Engine Oils 4T (Four-Stroke) are highly shear stable therefore eliminating viscosity breakdown. These products are Para synthetic multi-grade engine oils suitable for use in all seasons.

Typical Properties*

SAE J300 Viscosity Grade	10W-30	10W-40	20W-50
Appearance, Visual	Amber, Transparent, Liquid		
Viscosity @ 40°C, cSt, ASTM D445	69.55	97.25	160.55
Viscosity @ 100°C, cSt, ASTM D445	11.0	14.5	18.5
Viscosity Index, ASTM D2270	150	155	130
CCS Apparent Viscosity, cP, ASTM D5293	4,800@-25°C	5,200@-25°C	7,000@-15°C
MRV Apparent Viscosity, cP, ASTM D4684	16,000@-30°C	23,000@-30°C	18,000@-20°C
Flash Point, °C, ASTM D92	215	215	220
Pour Point, °C, ASTM D97	-42	-40	-30

**The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.*

Suitable for Use:

API SL
JASO MA2
JASO MA

Product Codes:

SAE 10W-30 – TFX190
SAE 10W-40 – TFX191
SAE 20W-50 – TFX192

