



TEXAS LUBE

Texas Optimum Multi-Purpose ATF

Product Description

Texas Optimum Multi-Purpose ATF is a quality automatic transmission fluid which is suitable for use in applications which require GM Dexron III or Ford Mercon specification fluids as well as most other pre-2006 ATF applications. This product is formulated with group II paraffinic base stocks and a performance additive package to provide adequate anti-shudder, anti-oxidant, anti-wear, and anti-foam properties. This oil is also suitable for use as a power steering fluid, hydraulic fluid, and/or industrial fluid when a “Dexron III/Mercon” type ATF is recommended.

Typical Properties*

<i>Parameter</i>	<i>Result</i>
Appearance, Visual	Red, Dyed, Liquid
Viscosity @ 40°C, cSt, ASTM D445	34.0
Viscosity @ 100°C, cSt, ASTM D445	7.10
Viscosity Index, ASTM D2270	178
Brookfield Viscosity @-40°C, ASTM D2983, cP	16,250
Flash Point, °C, ASTM D92	190
Pour Point, °C, ASTM D97	-48

**The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.*

Suitable for Use:

GM Dexron III-H, II-E, II
Ford Mercon
Allison C-4, TES-389

NOT Recommended for Ford Type F Fluids, or any ATF application specification newer than 2006, such as Dexron VI, Mercon V, or Mercon LV.

Product Code: T XM405

