



TEXAS LUBE

Texas Fortis

Synthetic Blend Heavy-Duty Engine Oils

SAE 25W-60; API CH-4/SN

Product Description

Texas Fortis Heavy-Duty Engine Oil 25w60 is a multi-grade lubricant designed for use in high speed four-stroke diesel engines as well as carbureted and gasoline engines in both heavy-duty and normal operating conditions. Formulated with anti-shear properties and Type I paraffinic base stocks and a special additive package designed for superior protection against wear, corrosion, oxidation and varnish. The API category CH-4 was introduced in 1998 for typical service for use in high speed four-stroke diesel engines designed to meet the '98 emission exhaust standards, using diesel fuel with 0.05% of sulfur content.

Typical Properties*

<i>SAE J300 Viscosity Grade</i>	<i>25W-60</i>
Appearance, Visual	Brilliant, Amber, Green
Viscosity @ 40°C, cSt, ASTM D445	208
Viscosity @ 100°C, cSt, ASTM D445	22.5
Viscosity Index, ASTM D2270	132
API Gravity ASTM D1298	29.9
Specific Gravity @ 15.6 °C ASTM D1298	0.887
Flash Point, C.O.C °C (°F) , ASTM D92	220(428)
Pour Point, °C (°F), ASTM D97	-24(-15)

*The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.

Meets, exceeds, or is suitable for use in the following specifications:

SAE 25W60

API CH-4/SL

TBN 9

Product Code:

SAE 25W-60 – TXF212

