Texas Primus Elite Euro SAE 5w-40; Full Synthetic Motor Oil ACEA A3/B4, API SN

Product Description

Texas Primus Elite Euro SAE 5W-40 Full Synthetic Motor Oil ACEA A3/B4, API SN is formulated with synthetic base oils and a premium additive package. This oil is designed for use in carbureted, fuel injected, turbocharged and supercharged gasoline engines. This oil exceeds the performance requirements of API SN and ACEA A3/B4.

Ivpical Properties*

| SAE J300 Viscosity Grade | 5W-40 |
|--|----------------------------|
| Appearance, Visual | Amber, Transparent, Liquid |
| Viscosity @ 40°C, cSt, ASTM D445 | 80.0 |
| Viscosity @ 100°C, cSt, ASTM D445 | 13.5 |
| Viscosity Index, ASTM D2270 | 172 |
| CCS Apparent Viscosity, dP, ASTM D5293 | 5,600@-30°C |
| MRV Apparent Viscosity, cP, ASTM D4684 | 23,000@-35°C |
| Flash Point, °C, ASTM D92 | 210 |
| Pour Point, °C, ASTM D97 | -42 |
| Total Base Number, mgKOH/g, ASTM D2896 | 10.5 |
| | |

^{*}The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.

Exceeds Performance Requirements

ACEA A3/B4-23 ACEA A3/B3-16 API SN/CF Porsche A40 MB 226.5 / 229.3 / 229.5 BMW LL-01 WW 502.00, 505.00 Renault RN0700 / RN0710

Product Code

TPE009

