



TEXAS LUBE

Texas Altum AW Hydraulic Oil ISO VG 22, 32, 46, 68 & 100

Product Description

Formulated with high viscosity-index paraffinic base stocks and premium performance additives, Texas Altum AW Hydraulic Oils ISO VG 22, 32, 46, 68, 100 exhibit excellent oxidation stability, corrosion protection, shear stability, and pumpability in a wide array of operating conditions and temperatures. The comprehensive additive package includes anti-wear, anti-corrosion, anti-foaming agents as well as detergency. Acceptable for a wide-range of applications, Texas Altum AW Hydraulic Oils ISO VG 22, 32, 46, 68, 100 resist oxidation, rust, corrosion, foaming, varnish, and wear.

Typical Properties*

ISO VG	22	32	46	68	100
Appearance, Visual	Yellow, Transparent, Liquid				
Viscosity @ 40°C, cSt, ASTM D445	22.0	32.0	46.0	68.0	100.0
Viscosity @ 100°C, cSt, ASTM D445	4.30	5.47	6.92	8.97	11.40
Viscosity Index, ASTM D2270	100	105	105	105	100
Flash Point, °C, ASTM D92	195	200	205	210	215
Pour Point, °C, ASTM D97	-20	-18	-15	-12	-10

**The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.*

Suitable for Use:

Parker Denison HF-0, HF-1, HF-2
MAG IAS P-69 (ISO 68)
MAG IAS P-68 (ISO 32)
MAG IAS P-70 (ISO 46)
GMLS-2
JCMAS HK
U.S. Steel 127
U.S. Steel 136
Bosch Rexroth RD90220
SAE MS1004

Product Codes:

ISO VG 22- TXA605
ISO VG 32 - TXA606
ISO VG 46 - TXA607
ISO VG 68 - TXA608
ISO VG 100 - TXA609

